

duravent[™]
GROUP

RUTLAND
TRUSTED SINCE 1883

HOME & HEARTH

RETAIL PRODUCT CATALOG



140+ YEARS OF INNOVATION





We offer a wide range of quality products to maintain, clean, and repair wood or gas stoves, fireplaces, hearths, and chimneys both indoors and outdoors, backed by 140+ years of expertise and innovation. Check out our new grill, household, and outdoor cleaning products!

CONTENTS

FIREPLACE & HEARTH

<i>FIRE STARTERS</i>	5-6
<i>RAINBOW FLAME® CRYSTALS</i>	6
<i>CREOSOTE & SOOT REMOVERS</i>	7-10
<i>ACCESSORIES & GLOVES</i>	11-12

MAINTENANCE

<i>CLEANERS</i>	15-16
<i>CEMENTS & MORTARS</i>	18-21
<i>FIREBRICKS</i>	22-23
<i>GASKETS & INSULATION</i>	24-25
<i>HOME & CHIMNEY CARE, PAINTS</i>	27
<i>POLISHES</i>	28
<i>SEALANTS & ADHESIVES</i>	29

BRUSHES & RODS

<i>BRUSHES</i>	31
<i>RODS & ADAPTERS</i>	32

INDEX	34
--------------	----

NEW ICONS

Look for these icons to easily identify Rutland's signature **DIY** categories & products, **CLEAN BY RUTLAND**, and our new **FINER FIRE COLLECTION™**.



FIREPLACE & HEARTH



FIRE STARTERS

SAFE LITE® FIRE STARTER SQUARES

Easy to light - even when wet - and burn up to 10 minutes per square! Only 1 - 2 squares are needed to start a fire. Simply break off 1 - 2 squares and set them on wood or pellets. Light by touching a flame to the rough edge of a square. These environmentally friendly, non-toxic squares are made of compressed recycled wood chips, paper fiber, and wax. Will not flavor food.

50B Carton of 144 Squares (8 per case)

50C Carton of 24 Squares (24 per case)

USE: BBQ, Grills, Smokers



SAFELITE 2X JUMBO FIRE STARTERS

Rutlands Jumbo Firestarters are the best to start a fire in the toughest conditions. 20 minute burn time. No flare ups.

50J (9 per case)

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



BBQ FIRE STARTERS

Made with vegetable wax. Light weight and portable. Burns up to 10 minutes. 100% natural materials.

50W (9 per case)

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



FIRE STARTERS

ONE MATCH® FIRE STARTER GEL - PATRIOT PACK

A clean burning, odor-free gelled fire starter for hard-working Americans. Safe for cooking over & won't flavor food when used for cooking All-American meals. The best fire starter for pellet stove owners - mix gel with pellets and ignite! Thicker than the rest, with this Top-Secret American formula, these colors don't run!

49USA (6 per case)

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



ONE MATCH® FIRE STARTER GEL

A thick, odor-free, gelled fire starter for quickly and easily starting any fire! Will not flavor food.

48 8 fl oz Bottle (12 per case)

49 16 fl oz Bottle (12 per case)

49Q 32 fl oz Bottle (12 per case)

USE: BBQ, Grills, Smokers



RAINBOW FLAME® CRYSTALS

RAINBOW FLAME® CRYSTALS

A family favorite – enjoy beautiful blue and green flames! Simply shake 1/2 cup, or toss the whole stick, onto a bed of hot coals. Not for use in gas units or in fires that will be used to prepare food.

715 1 lb Canister (12 per case)

715C 1.5 oz Short Toss-In Stick (36 per case)

USE: Fireplace, Fire Pit, Wood Stove, Outdoor, Indoor



RAINBOW FLAME® CRYSTALS

Add beautiful and long-lasting blue, green, and purple flames to your wood burning fire with convenient packets. Light weight and portable. Great for making backyard memories.

715P Craft Paper Toss-in Packets (25 per case)

71599 XL 2.5 lb cannister (6 per case)

USE: Fireplace, Fire Pit, Wood Stove, Outdoor, Indoor



WARNING: These products can expose you to harmful chemicals.
For more information, go to www.P65Warnings.ca.gov.

CREOSOTE REMOVERS

PELLET STOVE CREOSOTE REMOVER

Helps prevent dangerous creosote buildup in pellet stoves, wood stoves, and fireplaces. Concentrated creosote removing formula combined with high quality wood pellets dried to 2-5% moisture content. Recommended usage 2x/week

98P 8 oz Box (12 per case)

98P03 3 lb Bag (5 per case)

98P05 5 lb Bag (4 per case)



USE: Pellet Stove, Fireplace, Wood Stove



CREOSOTE ANTIDOTE

Helps prevent dangerous creosote buildup in wood stoves and fireplaces. Made with 100% recycled hardwood and powered by creosote concentrate technology.

98A 6 lb Box (2 per box)



USE: Fireplace, Wood Stove



CREOSOTE CONCENTRATE TOSS-IN PACKETS

Rutland's Powerful creosote remover in convenient toss in packets. Made with Craft Paper. Concentrate formula 3x.

97C5 5 Pack Box (60 per case)

97C20 20 Pack Display (8 per case)



USE: Pellet Stove, Fireplace, Wood Stove



CREOSOTE CONCENTRATE

Rutlands Powerful creosote remover in a convenient and economical tub. Two scoops per treatment.

19701 1 lb (12 per case)

19702 2 lb (6 per case)



USE: Fireplace, Wood Stove

WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.



CREOSOTE REMOVER CANISTERS (3-PACK)

Contains 3 canisters to prevent creosote build-up in chimneys. Safe to use in all chimneys and wood-burning appliances. Simply toss one canister onto a bed of hot coals to turn sticky, tar-like creosote into brushable ash and prevent further build-up from occurring. Canisters burn safely to ash. Use 1 or more canisters per week as needed. Will not damage catalytic converters.

97G Three 3 oz Canisters (12 per case)

USE: Fireplace, Wood Stove



CREOSOTE REMOVER

Keeps creosote build-up at bay! Add 1-2 scoops to a fire once per week or more often as needed. Safe for use in all chimneys and wood-burning appliances. Will not damage catalytic converters.

97 1 lb Tub (12 per case)

98 2 lb Tub (6 per case)

USE: Fireplace, Wood Stove



LIQUID CREOSOTE REMOVER

Great for all stove and flue types, but best for pellet stoves where granules fall through the burner pan. Spray on an existing fire or pre-treat fuel before adding to a fire to make a chimney safer and more efficient.

97L 32 fl oz Spray Bottle (6 per case)


USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor





IMPORTANT!

RECOMMENDED FREQUENCY OF SOOT/CREOSOTE REMOVER
USE BASED ON WOOD TYPE BURNED



SOFTWOODS


Aspen	Basswood
Balsam Fir	Box Elder
Cedar	Cottonwood
Pine	Hemlock
Poplar	Willow

LOW BTU

Burn at lower temperatures
Tend to be more porous woods
with oils and resins that coat
fireplace or stove in soot/creosote

RUTLAND Tip

Use soot/creosote remover
6-7 times per week



SOFT HARDWOODS


Birch	Hackberry
Cherry	Spruce
Douglas Fir	Sycamore
Elm	Walnut
Red Maple	Yew

MID BTU

May contain some oils and
resins that create some
soot/creosote

RUTLAND Tip

Use soot/creosote remover
2-3 times per week



HARDWOODS

Ash	Apple
Beech	Dogwood
Hickory	Hawthorn
Oak	Mulberry
Sugar Maple	Osage Orange

HIGH BTU

Burn at higher temperatures
Dry, dense woods that burn
cleanly and create very little
soot/creosote

RUTLAND Tip

Use soot/creosote remover
1 time per week

Estimates based on assumption that wood is burned daily during burn season. Actual BTUs may vary depending on region and specific type of wood.
The potential exists for creosote buildup regardless of the wood type used if the wood is burning below 200°F

KWIK-SHOT® SOOT STOPPER CANISTERS (3-PACK)

Contains 3 canisters to control soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Simply toss one canister onto a bed of hot coals to clean existing soot and prevent further deposits from forming. Canisters burn safely to ash. Use 1 or more canisters per week as needed.

100G Three 3 oz Canisters (12 per case)

USE: Fireplace, Wood Stove



SOOT SWEEP® SOOT DESTROYER®

Controls soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Add 1-2 scoops to a fire once per week or more often as needed.

100 1 lb Tub (12 per case)

100B 2 lb Tub (6 per case)

USE: Fireplace, Wood Stove



LOG BRIGHT® GAS LOG SOOT REMOVER

Spray on gas fireplace logs to safely remove and control future soot buildup, giving them a “like new” appearance. Easy to use, this spray-on cleaner does not require scrubbing or wiping off. Use on vented and vent-free liquid propane and natural gas units. Will not discolor ceramic logs or harm burners. Do not use on white birch or fiber logs.

570-6 16 fl oz Spray Bottle (6 per case)



USE: Gas Fireplace



BURN INDICATOR

Monitors the performance of a wood- or coal-burning stove. See the potential for creosote build-up at a glance. Magnetically attaches to vertical, single-wall pipe or cooktop surface of a wood or coal stove. Indicates overheating or low-temperature creosote build-up hazard.

701-6 1 Magnetic Burn Indicator (6 per case)

USE: Wood Stove, Coal Stove, Indoor



STACK-N-STORE™ STEEL BRACKETS

Set of four heavy-duty, powder-coated corner brackets for building storage racks, shelves, and worktops in almost any size. Build a wood box to keep firewood off the ground to improve drying and to keep it away from pests and decay, or using more than one set, create storage shelves. Just screw or nail these brackets to any length of 2" x 4" lumber and the possibilities are endless!

30360R 4 Brackets Per Box (6 per case)



FIREPLACE GLOVES

Made from genuine cowhide leather and lined with cotton fabric. Gloves have a cuff that extends up the forearm for additional protection. Use for fireplaces, wood stoves, grills, and fire pits. These gloves are NOT rated fireproof or flame resistant. To prevent injury, avoid direct contact with open flames or smoldering embers. One size fits most. Red.

702 1 Pair of Gloves



SILICA SAND

Our Silica Sand is ideal for all gas burning fire pits and fire places (except Liquid Propane). This striking Natural Silica Sand Enhances the natural beauty of fire, while modernizing classic looks.

15810 13 lb pail (2 per case)

USE: Gas Burning Fire Pits & Fire Places



OSCILLATING HEAT-POWERED WOOD STOVE FAN

5-blade, 60° oscillating, heat-powered wood stove fan generates its own electricity from the heat of the stove. The fan starts automatically. The hotter the stove, the faster the fan blades rotate resulting in more air circulated. Rutland's fans increase stove efficiency, decrease fuel usage, and warm rooms faster all with near silent operation. Designed for freestanding stoves with normal surface temperatures ranging between 122 – 650° F. Needs no Electricity, Cords or Batteries. This powerful fan provides an industry leading 220 CFM!

FN05 1 per case

USE: Wood Stove



FIRE BLANKET

A tried-and-true solution to quickly, and easily extinguish small fires. Rutland's Fire Blanket is a woven fiberglass used to smother fires by depriving it of oxygen. The best solution for liquid or grease fires, but will work on ordinary combustible fires, like wood fires. Ensure proper fire safety and peace of mind by keeping one accessible in any cooking area, fire pit or fireplace, or vehicles. Unlike traditional fire spray extinguishers, fire blankets are easily stored and accessible, will never expire, and non-mechanical, so there's no potential of it breaking while it's stored away. Rutland's Fire Blanket is composed of strong woven fiberglass fabric, and features straps for quick and intuitive deployment. Each fire blanket measures 40" x 40".

10911 1-pack

19112 2-pack

19114 4-pack

12911 12-pack display



HOT DOG SNOW & ICE MELT

Our Ice Melt draws moisture from the air and ice while generating heat, which enables it to work when other deicers cannot at temperatures down to -25°F. This deicer is safe to use around pets, on concrete, and vegetation when used correctly. Covers up to 5000 sq. ft. Calcium Chloride formulated to be environmentally safe and easily spreadable. Concentrated formula guarantees long-term, maximum effectiveness from season to season. Non-corrosive & non-conductive.

HD10 10 lb jug (2 per case)

HD10BG 10 lb bag (2 per case)

USE: Driveways, Sidewalks, Porches, Patios





MAINTENANCE



FIREPLACE & WOOD STOVE GLASS CLEANER

Formulated to remove smoke, soot, and creosote residue from glass doors of fireplaces and wood stoves. Spray-on cleaner does not contain dangerous acids or ammonia. Just spray on and wipe off – it's that easy! In no time at all, fireplace or stove glass will have that "like-new" appearance for continued enjoyment of leisure fires.

82 32 fl oz Spray Bottle (6 per case)



CLEAR GLASS STOVE, GRILL & HEARTH CONDITIONING GLASS CLEANER

Non-scratching formula consisting of micro-scrubbers that remove baked-on soot, creosote, carbon, and other mineral residues from glass doors of fireplace inserts, and coal-, oil-, and wood-burning stoves and pellet stoves. Ammonia-free. Leaves behind a protective silicone layer to make future cleanings even easier!

84 8 fl oz Bottle (12 per case)



MULTI-SURFACE PRO CLEAN

This versatile cleaner conditions, cleans, and protects a variety of surfaces. The ammonia-free formula is perfect for use on glass, thermal glass, stainless steel, chrome, aluminum, porcelain, tile, ceramic range top, oven doors, sealed stone, kerosene heater glass, and fiberglass shower doors. Clean citrus scent. NOT for use on cars, windows, plastic (ex. microwave oven doors), plexiglass, stainless look or chrome look finishes.

185 8 fl oz Bottle (12 per case)



WHITE-OFF® GLASS CLEANING CREAM

Specially formulated for the removal of white residue on gas log fireplace glass doors. Non-abrasive and easy to use, this glass cleaning cream does not scratch or cause micropitting. Ammonia-free.

565 8 fl oz Bottle (12 per case)



BRICK & STONE CLEANER

Removes stubborn creosote or soot build-up on bricks or stone surrounding a fireplace. Industrial strength solvent will penetrate and dissolve build-up on most any stone or sealed brick without use of dangerous acids. Can also be used on an asphalt roof to remove chimney smoke and grime.

83-6 16 fl oz Spray Bottle (6 per case)



TSP CLEAN & PREP®

Heavy-duty indoor, outdoor cleaner & degreaser. Cleans and prepares surfaces for painting by allowing for superior adhesion. Great for woodwork, walls, decking, siding, and concrete & masonry. Helps fight mold & mildew, removes heavy deposits of grease & grime, smoke, soot stains, and chalked paint. Use to clean lead-contaminated dust from surfaces. Can be combined with bleach for an even stronger solution. Use phosphate-free product in areas where use of phosphate is strictly regulated. For heavy duty indoor cleaning, dissolve 2 scoops in 1 gallon of hot water.

CLTSP01 Technical-grade Trisodium Phosphate
16 oz. bag (15 per case)

CLTS01 Phosphate-free for heavier outdoor use
16 oz. bag (15 per case)

USE: Woodwork, Walls, Decking, Siding, Concrete & Masonry



JUST GRATE®

Grill grate and BBQ cleaner makes cleaning your grill easy. The powerful formula quickly gets rid of caked on food, carbon, grease, and baked on deposits that can ruin the taste of your favorite foods. Fresh citrus scent.

462 16 oz bottle (6 per case)

USE: Grill grates & BBQs







CEMENTS & MORTARS

	CURE	STICKS TO	INDOOR/OUTDOOR	TEMP	APPLICATION
NAME	TYPE	MASONRY/METAL	USE	RATING (F)	LAYER*
FIREPLACE MORTAR (63, 63B, 63G)	HEAT CURE	MASONRY	INDOOR	2000°	1/8" - 1/4"
BLACK FURNACE CEMENT (64A, 64C, 64, 65)	HEAT CURE	BOTH	INDOOR	2000°	UP TO 1/8"
STOVE & GASKET CEMENT (77, 78)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
FIBERGLASS GASKET CEMENT (77E, 78E)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
CHIMNEY MASONRY PATCH (89)	AIR DRY	MASONRY	BOTH	200°	1/8" - 1/2"
DRY MIX 211 (211)	AIR DRY	MASONRY	BOTH	2550°	1/16" - 1"
CASTABLE REFRACTORY CEMENT (600, 601)	AIR DRY	MASONRY	BOTH	2200°	1/2" - 9"
REFRACTORY CEMENT (610, 611)	HEAT CURE	MASONRY	INDOOR	2000°	UP TO 1/4"
STOVO (615)	HEAT CURE	BOTH	INDOOR	2000°	1/8" - 1/4"
PIPE INSULATING CEMENT (623)	AIR DRY	BOTH	INDOOR	300°	1/2" +

HEAT CURE: Allow to air-dry for 24 hours. Burn a low ~250°F fire for about 2 hours, then build the fire up to ~500°F for an additional hour. Learn more about heat curing and watch demonstrations:



Scan to view our
Cements & Mortars
Minute Clinic.



E-Z SPREAD FIBERGLASS STOVE GASKET CEMENT

Designed to be the easiest gasket cement for affixing fiberglass gaskets to steel and cast iron. Very easy to spread and control application and will not expand or contract during continued use. Apply in beads of 1/8" or less. 2000°F temperature rating. New and improved, no longer requires heat cure. Black.

77E 2.3 fl oz Tube (12 per case)

78E 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



STOVE & GASKET CEMENT - THE ORIGINAL

This cement pulls double duty because not only can this cement adhere any fiberglass gasket to most any metal, it can also be used to fix those small cracks, pinholes, and leaks in a cast iron stove. Available in a handy squeeze tube or in a larger caulk gun-ready size, this cement will help restore a stove to safe and efficient operation. Apply in beads of 1/8" or less. 2000°F temperature rating. Black.

77 2.3 fl oz Tube (12 per case)

78 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



REFRACTORY CEMENT

An ideal high-heat cement for masonry joints 1/4" or less. Pre-mixed, easy to trowel, and fiber reinforced, this cement can be used to set, bond, and repair cracked or broken firebricks in stoves, fireplaces, and furnaces as well as for building fireplace boxes. Its thick, smooth consistency makes this cement perfect for use as mortar between firebricks. Meets ASTM E136-04. 2000°F temperature rating. Requires heat cure. Buff.

610 64 fl oz Tub (6 per case)

611 128 fl oz Pail (2 per case)



Heat Cure Required



USE: Fireplace, Wood Stove, Indoor





CASTABLE REFRACTORY CEMENT

An exceptionally strong dry-mix cement that chemically sets and dries as hard as brick. Just add water! Perfect for casting into custom designs because it holds its shape while drying. Can even be used as the sole material when casting a solid stove bed or outdoor oven. 2200°F temperature rating. Does not require heat cure! Cast up to 9" depth. Color may vary.

600 12.5 lb Pail (2 per case)

601 25 lb Pail (1 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor



FURNACE CEMENT

Premixed and ready to use, this is one of the easiest cements to apply. Use this smooth consistency cement to bond and seal metal to metal or metal to masonry joints less than 1/8". Repair a crack, seal the collar to the top of a wood stove, or seal between firebricks and prefabricated fireplace. Use anywhere a quality high-temperature adhesive is required for furnaces, firebrick repair, filling gaps, sealing joints, or gluing ceramic logs. Adheres to metal, stone, and firebricks, creating a permanent smoke- and gas-tight seal. 2000°F temperature rating. Heat cure required.

64A 8 fl oz Tub (12 per case)

64C 10.3 fl oz Cartridge (12 per case)

64 16 fl oz Tub (12 per case)

65 32 fl oz Tub (6 per case)

 Heat Cure Required



HEAT TRAPPER™

RUTLAND Heat Trapper is a lightweight, low-density cement for high heat insulation. It's the ideal refractory cement for pizza ovens, tandoor ovens and BBQs because it is designed to keep the heat inside the burn area. Needs to be mixed with water, and will adhere to masonry, terracotta, fire clay and fire bricks.

10501 12 lb Tub





STOVO® STOVE MORTAR

Ready-to-use, premixed, and general-purpose for repairing or relining firebrick in interior stoves, furnaces, boilers, incinerators, Franklin stoves, barbecues, and fireplaces. Adheres to metal or masonry and will prevent air and gas leaks around flue and chimney joints, ash pit doors, and small cracks between bricks and linings. Apply in layers 1/4" or less and allow to air dry for 24 hours between layers. 2000°F temperature rating. Requires heat cure. Buff.

 Heat Cure Required



615 32 oz Tub (6 per case)

USE: Fireplace, Wood Stove, Indoor



FIREPLACE MORTAR

Perfect for repairing small chips or cracked firebrick, re-pointing mortar joints between firebricks, and bonding firebricks together. Adheres masonry to masonry for brick, firebrick, and stone. Use for cracks 1/8" deep or less. If deeper, apply multiple layers of ~1/8" and allow 24 hours to dry between layers. Easy to apply with a caulking gun and will last for years. Sets as hard and as strong as firebrick after curing and can withstand the high temperatures produced by a wood fire. 2000°F temperature rating. Requires heat cure.

 Heat Cure Required



63 Black 10.3 fl oz Cartridge (12 per case)

63B Buff 10.3 fl oz Cartridge (12 per case)

63G Gray 10.3 fl oz Cartridge (12 per case)

USE: Fireplace, Wood Stove, Indoor



DRY MIX 211®

A refractory mortar ideal for joining or repairing masonry flue tile in any gas or wood fireplace and wood, coal, or pellet stove chimney. Just add water, mix, and trowel on to seal and join flue tiles. It can also be used as a parge coating (thin over-coat) when building fireboxes to give a fireplace a nice, even, dark gray finish. Meets NFPA 211 Standards and NYSCMA Tek 4.0 Specifications. 2550°F temperature rating. Does not require (but is stronger with) heat cure. If applying in layers, do not exceed 1" per layer and allow 24 hours to dry between layers. Dark Gray.



21125 2.5 lb tub (6 per case)

211 10 lb Pail (4 per case)

USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Outdoor, Indoor



FIREBRICK & MORTAR KIT

Kit includes 5 Firebox Bricks and 2 lbs Dry Mix 211. Our Firebox Bricks are perfect for intermediate duty for building new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). They can also be used to line a fire pit in the backyard or anywhere else a brick is needed that can withstand high temperatures. Bricks measure 9" x 4-1/2" x 1-1/4".



KT603211 5 bricks, 2 lbs. mortar per case

USE: Outdoor, Indoor





FIREBOX BRICKS

These firebricks can be used to build new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). Color may vary. They can also be used to line a fire pit in the backyard or anywhere else a brick is needed that can withstand high temperatures up to 2700°F. Each brick measures 9" x 4.5" x 1.25".

604-1 Buff 6 Bricks per case



USE: Outdoor, Indoor

WARNING: These products can expose you to harmful chemicals.
For more information, go to www.P65Warnings.ca.gov.



FIREBOX BRICKS

These firebricks can be used to build new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). Color may vary. They can also be used to line a fire pit in the backyard or anywhere else a brick is needed. Meets or exceeds residential building codes regarding fireplace and chimney construction. Color may slightly vary. Not for direct food contact. Each brick measures 9" x 4.5" x 1.25".

603-1 6 Bricks per case - Ivory

10602 6 Bricks per case - Red



USE: Outdoor, Indoor



SOAP SPLIT FIRE BRICKS

Slender fire bricks half the size of typical fire bricks. Commonly used for decorative fireplace designs, such as herringbone or chevron designs, but can also be used to build or repair outdoor fire pits, pizza ovens and stove linings. Meets ASTM C-27 (Low Duty), C-1261 and the requirements of national & international building codes regarding fireplace and chimney construction. Color may slightly vary. Not for direct food contact. Each brick measures 9" x 2.25" x 1.25".

16035 12 Bricks per case - Ivory

160250 12 Bricks per case - Red



USE: Outdoor, Indoor





SOAPSTONE FIRE BRICKS

Rutland's Soapstone Fire Bricks provide a **food-safe** surface and are best-in-class for the absorption and retention of heat. Incredibly dense, heavy fire bricks that will easily withstand temperatures produced by any wood fires, radiating heat much longer than clay fire bricks. Featured in high-end pizza ovens and masonry heaters, soapstone adds a natural and unique beauty along with improved performance. The ideal fire brick for pizza ovens, but works great for fireplaces, surrounds, and outdoor BBQ pits. Each brick measures 9" x 4.5" x 1.25".

16051 **6 Bricks per case - Blue-gray**



Uses: Outdoor, Indoor, **Food-Safe Surface**





PREMIUM SELF-ADHESIVE CERAMIC GRILL REPLACEMENT GASKET

Ceramic Grill and Smoker gasket replacement. Fits sizes XXL, XL, Large, Medium, Small and Mini. Premium gasket intended for Big Green Egg and similarly sized grills. Designed to comfortably endure 5+ clean burns at 700°F. High heat-resistant self-adhesive strip featuring 3M technology. White Fiberglass, longer lasting and more durable than Nomex and felt gasketing. Bonus gasketing included for replacing the chimney seal.

99N12	12' (15 per case)
99N12G	12' (15 per case)
99N17	17' (15 per case)
99N17G	17' (15 per case)



 Scan to view installation instructions.

FIBERGLASS INSULATION

An insulation strip with a peel-off, self-adhesive backing that is ideal for forming a smoke- and gas-tight seal between a fireplace insert and existing masonry. For the best performance, replace insulation every time the insert is removed for cleaning. Rated to 250°F.

105	10' Roll (6 per case)
-----	-----------------------



GRAPHO-GLAS® STOVE GASKETS

Graphite impregnated, braided fiberglass gasketing engineered to provide superior sealing, protection, and longevity. Also resist abrasion, creosote and soot adhesion, and temperatures up to 1000°F. Used by major stove manufacturers and to replace worn-out gaskets in wood and coal stoves or fireplace inserts. Annual replacement of stove gaskets ensures a tight seal for maximum airtight operation and efficiency.

KITS (Includes Gasket & Fiberglass Stove Gasket Cement) (6 per case)

95A-6	7' x 5/16"	Rope
95-6	7' x 5/8" x 3/16"	Flat
95W-6	7' x 3/4" x 1/4"	Flat
96-6	7' x 3/8"	Rope
96N-6	7' x 1/2"	Rope
96W-6	7' x 5/8"	Rope
99-6	7' x 3/4"	Rope
99N-6	7' x 7/8"	Rope



BAGGED (Cement not included)

90	7' x 5/8" x 3/16"	Flat
91	7' x 3/8"	Rope
91N	7' x 1/4" - 5/16"	Rope
92	5' x 1/2" - 5/8"	Rope

92W	7' x 3/4"	Rope
94N	5'4" x 7/8"	Rope
94	6' x 1"	Rope



SPOOLS

720	157' x 5/8" x 3/16"	Flat
721	200' x 5/16"	Rope
721N	200' x 1/4"	Rope
722	132' x 3/8"	Rope
723	88' x 1/2"	Rope
723W	100' x 7/16"	Rope

724	65' x 5/8"	Rope
725	47' x 3/4"	Rope
725W	40' x 7/8"	Rope
726	25' x 1"	Rope
516GG	75' x 5/16"	Griddle Gasket



WHITE FIBERGLASS GASKETS SPOOLS

721P	200' x 5/16"	Rope
726P	25' x 1"	Rope
78LA	25' x 7/8"	Lopi Rope

GASKET SPOOL DISPLAY

Holds 5-6 gasket spools with convenient measuring tape. Black.

108E 24" x 12"



STOVE WINDOW GASKETS

Designed to securely seal stove window glass in stove doors and openings. Peel off protective paper and wrap self-adhesive tape over the glass edge. No additional cement is needed. Available in Black with graphite or White.

93	Black	4'6" x 11/16"	Bagged (12 per case)
727	Black	80' x 11/16"	Spoiled (1 per case)
727P	White	80' x 13/16"	Spoiled (1 per case)
729	Black	90' x 13/16"	Spoiled (1 per case)



Scan to view our video illustrating how to replace a stove door gasket.



WARNING: These products can expose you to harmful chemicals. For more information, go to www.P65Warnings.ca.gov.





WATER GLASS CEMENT FLOOR SEALER

This unique formula is a multi-use sealant and adhesive. When diluted, it becomes an excellent stain-resistant concrete sealant against oils while simultaneously preventing concrete dust. Use full-strength for an effective and inexpensive adhesive for sealing gaskets, cartons, and applying labels.

146 1 gal Jug (4 per case)

USE: Indoor



PAINTS



HI-TEMP PAINTS

Provide both a beautiful flat black finish as well as durability to any stove or grill, and will look great for years while keeping rust at bay. Use outdoors or indoors. Adhere to steel, cast iron, aluminum, and brick, and are great for grills, stoves, smokers, stove pipes, fireplace inserts, furnaces, barbecues, mailboxes, lampposts, fireplace tools, brass, firebrick, and chimney caps. Flat Black.

PREMIUM 1400°F BRUSH-ON PAINT WITH LOW VOC

81V 16 fl oz Can (6 per case)

1200°F HI-TEMP PAINTS

80 12 fl oz Spray Can (12 per case)

81 16 fl oz Can* (6 per case)

**Product 81 not for sale in California*

USE: Outdoor, Indoor




STOVE POLISH *not for sale in California*

Transforms old, dull, cast iron stoves into like-new appearance! Combines three different waxes with some of the blackest pigments to renew and protect cast iron. Non-toxic and non-flammable, this polish can be buffed to a deep lustrous glow, leaving cast iron looking better than new. Prevents deterioration to the exteriors of stoves, grills, ornamental ironwork, and heating accessories even during extended storage. Not for use on painted, powder-coated, stainless, raw, or sandblasted steel. Black.

70 2.3 fl oz Tube (12 per case)



USE: Outdoor, Indoor


LIQUID STOVE & GRILL POLISH *not for sale in California*

Protects cast iron and steel heating and cooking appliances from getting dull and rusty. Apply polish and buff to a high luster to restore that like-new appearance. Safe to use – non-flammable and non-toxic. One bottle should lightly polish an average sized, free-standing wood stove or a large grill. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Black.

72 8 fl oz Bottle (12 per case)



USE: Outdoor, Indoor


WILLIAM'S® STOVE POLISH *not for sale in California*

Brings a low-luster, dark gray finish to any unpainted cast iron appliances. Easy to apply. Buff after drying. Can also be used on wood and coal stoves, barbecues, hibachis, iron pots, iron kettles, and grills. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Dark Gray.

WI-00710 2.3 fl oz Tube (12 per case)



USE: Outdoor, Indoor





SEAL IT RIGHT® FLEXIBLE LATEX SEALANT *not for sale in California*

A non-permanent seal that expands and contracts with heat variations. For use with metal and aluminum. Use to install and maintain direct vent appliances, gas-burning systems, pellet stoves, and metal flues on wood and coal stoves. Easily removed for cleaning and inspection. Not an adhesive. 800°F continuous temperature rating. Black. Does not require a heat cure.

641C 2.3 fl oz Tube (12 per case)

641 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



HIGH HEAT SILICONE SEALANT

A great solution for sealant needs – seals off gases and smoke permanently, with limitless uses in the home or on job sites. Use to seal fireplace inserts, repair solar panels, or seal a chimney cap to withstand wind, rain, and hot smoke. Available in 600°F RTV and 500°F RTV temperature ratings and two colors (Red and Black) as well as Clear. Does not require a heat cure.

600°F RTV

600°F RTV temperature rating and available in Red and Black.

76R Red 10.3 fl oz Cartridge (12 per case)

76B Black 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



500°F RTV

500°F RTV temperature rating and available in Black and Clear. Choose from a handy 2.7 fl oz tube for small repairs or a 10.3 fl oz caulk gun cartridge for larger jobs.

76 Black 10.3 fl oz Cartridge (12 per case)

76A Black 2.7 fl oz Tube (12 per case)

76C* Clear 10.3 fl oz Cartridge (12 per case)



**Food safe, FDA regulation #21 CFR 177.2600.*



BRUSHES & RODS





CHIMNEY SWEEP® WIRE CHIMNEY BRUSHES

Designed with the homeowner in mind, these brushes have an open, single spiral construction with 6" of fill, plated shafts, and 1/4" NPT threading for easy coupling with fiberglass rods or pull rings. Oil-tempered spring wire. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.

ROUND WIRE

16406	6"	Round (4 per case)
16407	7"	Round (4 per case)
16408	8"	Round (4 per case)
16409	9"	Round (1 per case)
16410	10"	Round (1 per case)

SQUARE WIRE

16506	6"	Square (4 per case)
16507	7"	Square (4 per case)
16508	8"	Square (4 per case)
16510	10"	Square (1 per case)
16511	11"	Square (1 per case)
16512	12"	Square (1 per case)

RECTANGULAR WIRE

36531	6" x 10"	Rectangular (1 per case)
16532	7" x 11"	Rectangular (1 per case)
16533	8" x 12"	Rectangular (1 per case)

CHIMNEY SWEEP® ROUND POLY CHIMNEY BRUSHES

Specially designed for stainless steel, liners, and stove pipes. These sturdy poly brushes have 6" of fill and are acid resistant. Fittings are 1/4" NPT threading. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.

16906	6"	Round Poly (4 per case)
16908	8"	Round Poly (4 per case)

CHIMNEY SWEEP® PELLET STOVE & DRYER VENT BRUSHES

Designed to clean both pellet stove vents and dryer vents. Brushes can easily navigate a sharp turning radius without getting caught in elbows. Brush filament is 0.020" poly. For light cleaning only. For heavier buildups, use RUTLAND® Pellet Stove Brushes PS-3, PS-4, or PS-5, shown below.

17409	3"	Brush with 10' Flexible Handle (4 per case)
17410	4"	Brush with 10' Flexible Handle (4 per case)
17419	3"	Brush with 20' Flexible Handle (4 per case)
17420	4"	Brush with 20' Flexible Handle (4 per case)

CHIMNEY SWEEP® PELLET STOVE BRUSHES

Made with poly bristles and available in 3", 4", and 5" round sizes. Heavy-duty ball tip guides brushes through narrow offsets and bends. Designed for heavy cleaning. Fittings are 1/4-20 thread. Use with RUTLAND® Rods 25P-5 and PSR-20 on page 24.

PS-3	3"	Round Poly (4 per case)
PS-4	4"	Round Poly (4 per case)
PS-5	5"	Round Poly (1 per case)



Tip: Be sure to match the fitting of brushes and rods (NPT - NPT or 1/4-20 - 1/4-20). Use a **Rutland Reducer** to allow the use of mismatched brushes and rods!





FIBERGLASS CHIMNEY BRUSH EXTENSION RODS

Designed with the DIY homeowner in mind. Rods are available individually in lengths of 4' and 6' and use 1/4" NPT threading to connect to a chimney brush. Attach to a RUTLAND® Chimney Sweep® Wire or Poly Brush to clean a chimney from the top down or up through the open fireplace. The fiberglass is flexible enough to handle slight offsets, but not enough to bend around sharp corners. Cleaning in an up-and-down motion with these rods will provide the power necessary for a satisfactory result.

10624	4'	Individual Rod	Bends <90° (24 per case)
10672	6'	Individual Rod	Bends 90° (24 per case)
KRK-18	18'	Kit (Six 3' Rods)	Bends 45° (5 per case)



FLEXIBLE POLY PELLET STOVE RODS

Poly rods designed to easily maneuver through 30° and 45° offsets, 0.250" diameter and 1/4-20 thread. Use with RUTLAND® Chimney Sweep® Pellet Stove Brushes.

25P-5	5'	Individual Rod	Bends 360° (10 per case)
PSR-20	20'	Kit (Eight 2.5' Rods)	Bends 360° (5 per case)



PULL RING - HOMEOWNER

Designed for the DIY homeowner to attach to RUTLAND® Extension Rods to provide an attachment point for ropes to pull RUTLAND® Chimney Sweep® Cleaning Brushes through a chimney during cleaning. Available with 1/4" NPT threading.

16202	1/4" NPT	(12 per case)
W38PTL	3/8" NPT	(12 per case)



REDUCER

Allows use of mismatched brushes and rods. Female connectors on both sides will adapt a brush and rod set to match each other. Product 1438 converts 1/4" NPT to 3/8" NPT, and 1439 converts 1/4" NPT to 1/4-20 threading.

1438	1/4" to 3/8" NPT	(12 per case)
1439	1/4" NPT to 1/4-20 Threading	(5 per case)





PRODUCT INDEX

PRODUCT #	PAGE #	PRODUCT #	PAGE #	PRODUCT #	PAGE #
98P	7	82	15	93	25
98P03	7	84	15	727	25
98P05	7	185	15	727P	25
98A	7	565	15	729	25
97C5	7	83-6	16	146	27
97C20	7	77E	19	81V	27
19701	7	78E	19	80	27
19702	7	77	19	81	27
FN05	12	78	19	70	28
49USA	6	610	19	72	28
50J	5	611	19	WI-00710	28
50W	5	600	20	641C	29
715P	6	601	20	641	29
71599	6	64A	20	76R	29
99N12	24	64C	20	76B	29
99N12G	24	64	20	76	29
99N217	24	65	20	76A	29
99N217G	24	615	21	76C	29
21125	21	63	21	16406	31
KT603211	21	63B	21	16407	31
10501	20	63G	21	16408	31
603-1	22	211	21	16409	31
10602	22	604-1	22	16410	31
16035	22	105	24	16506	31
160250	22	95A-6	25	16507	31
16051	23	95-6	25	16508	31
CLTSP01	16	95W-6	25	16510	31
CLTS01	16	96-6	25	16511	31
462	16	96N-6	25	16512	31
10911	12	96W-6	25	36531	31
19112	12	99-6	25	16532	31
19114	12	99N-6	25	16533	31
12911	12	90	25	16906	31
HD10	12	91	25	16908	31
HD10BG	12	91N	25	17409	31
15810	11	92	25	17410	31
50B	5	92W	25	17419	31
50C	5	94N	25	17420	31
48	6	94	25	PS-3	31
49	6	720	25	PS-4	31
49Q	6	721	25	PS-5	31
715	6	721N	25	10624	32
715C	6	722	25	10672	32
97G	8	723	25	KRK-18	32
97	8	723W	25	25P-5	32
98	8	724	25	PSR-20	32
97L	8	725	25	16202	32
100G	10	725W	25	W38PTL	32
100	10	726	25	1438	32
100B	10	516GG	25	1439	32
570-6	10	721P	25		
701-6	11	726P	25		
30360R	11	78LA	25		
702	11	108E	25		



duravent[™]
GROUP

RUTLAND
TRUSTED SINCE 1883

CONTACT DURAVENT CUSTOMER SERVICE
TO SPEAK WITH ONE OF OUR EXPERIENCED PROFESSIONALS!

800.252.8467 . retail@duraventgroup.com . duraventgroup.com/rutland . 10/2025



AMERIVENT®

duravent[™]

HART

COOLEY®



SELKIRK®

©2025 Duravent Group.

Chimney Sweep, Grapho-Glas, Seal it Right, One Match, Rainbow Flame, Dry Mix 211, Kwik-Shot, Log Bright, Soot Sweep, White-Off, and Soot Destroyer are registered trademarks of Rutland.

RUTLAND_Retail_CT001E_10-2025